

### STANDARD FEATURES

- Available in 40mm, 50mm, 63mm and 100mm sizes
- Stainless steel case and ring with plastic window
- 1/8" NPT back connection available in 40mm size; 1/4" NPT lower and back connection available in 50mm and 63mm sizes; 1/4" NPT lower connection available in 100mm size
- Dual scale dials with bar/kPa in blue (inner scale); psi in black (outer scale); on white background
- Panel mount kits available

### CATALOG NUMBERS

Dial Size	40mm	50mm	63mm	100mm
Connection Location	Back	Back	Bottom	Bottom
Connection NPT	1/8"	1/4"	1/4"	1/4"
Range (psi/bar/kPa)				
30"/0" vac. and -1/0 bar (-100/0 kPa)	BY40YVC8CW	BY41YVC4CW	BY41YVC4LW	BY42YVC4CW
30"/0/30 psi and -1/0/2 bar (-100/0/200 kPa)	—	—	—	BY42YCB4CW
30"/0/60 psi and -1/0/4 bar (-100/0/400 kPa)	BY40YCC8CW	BY41YCC4CW	BY41YCC4LW	BY42YCC4CW
30"/0/150 psi and -1/0/10 bar (-100/0/1000 kPa)	—	—	—	BY42YCE4CW
0-15 psi and 0/1 bar (100 kPa)	—	—	—	BY42YPC4CW
0-30 psi and 0/2 bar (200 kPa)	BY40YPD8CW	BY41YPD4CW	BY41YPD4LW	BY42YPD4CW
0-60 psi and 0/4 bar (400 kPa)	BY40YPE8CW	BY41YPE4CW	BY41YPE4LW	BY42YPE4CW
0-100 psi and 0/7 bar (700 kPa)	BY40YPF8CW	BY41YPF4CW	BY41YPF4LW	BY42YPF4CW
0-160 psi and 0/11 bar (1100 kPa)	BY40YPG8CW	BY41YPG4CW	BY41YPG4LW	BY42YPG4CW
0-200 psi and 0/14 bar (1400 kPa)	—	—	—	BY42YPH4CW
0-300 psi and 0/21 bar (2100 kPa)	BY40YPJ8CW	BY41YPJ4CW	BY41YPJ4LW	BY42YPJ4CW
0-600 psi and 0/42 bar (4200 kPa)	—	—	—	BY42YPM4CW
0-1000 psi and 0/70 bar (7000 kPa)	BY40YPP8CW	BY41YPP4CW	BY41YPP4LW	BY42YPP4CW
0-2000 psi and 0/140 bar (14,000 kPa)	—	—	—	BY42YPS4CW
0-3000 psi and 0/210 bar (21,000 kPa)	BY40YPT8CW	BY41YPT4CW	BY41YPT4LW	BY42YPT4CW
0-5000 psi and 0/350 bar (35,000 kPa)	BY40YPV8CW	BY41YPV4CW	BY41YPV4LW	BY42YPV4CW
0/10,000 psi and 0/700 bar (70,000 kPa)	—	BY41YPP4CW	BY41YPP4LW	BY42YPP4CW

To order, specify 10-digit "catalog number" from above table. For panel mount gauges (back connection only) add "-UC" to 10-digit catalog number.

### GAUGE DIMENSIONS BY40Y, BY41Y, BY42Y, BY45Y

Lower Connection Gauge Size/Type		A	B	C	D-1/4"	E	F	
50 mm	BY41Y	Inch	2.21	1.11	1.86	0.37	2.01	
		mm	56	28	47	9	51	
63 mm	BY42Y	Inch	2.62	1.13	2.08	0.39	2.45	
		mm	66	29	53	10	75	
100 mm	BY45Y	Inch	4.29	1.42	3.14	0.46	3.88	
		mm	109	36	80	12	98	
Back Connection Gauge Size/Type		A	B	F	G	H		
40 mm	BY40Y	Inch	1.78	1.00	1.61	1.62	1/8"	
		mm	45	25	41	41		
50 mm	BY41Y	Inch	2.21	1.11	2.02	2.05	1/4"	
		mm	56	28	51	52		
63 mm	BY42Y	Inch	2.62	1.13	2.45	2.05	1/4"	
		mm	66	29	62	52		

### PANEL MOUNT ASSEMBLY FOR 40mm, 50mm, 63mm GAUGES

Part No.		A	B	C	D	E	F	G	H	J	K
40mm Clamp	Inch	2.36	1.02	1.89	0.45	0.44	0.94	0.94	0.20	0.10	M5X0.8
	mm	60	26	48	11.6	11.3	24	24	5	2.50	M5X0.8
50mm Clamp	Inch	2.83	1.26	2.36	0.57	0.56	0.47	1.18	0.24	0.10	M5X0.8
	mm	72	32	60	14.6	14.2	30	72	6	2.50	M5X0.8
63mm Clamp	Inch	3.27	1.26	2.80	0.57	0.56	0.47	1.40	0.24	0.10	M5X0.8
	mm	83	32	71	14.6	14.2	12	35.5	6	2.50	M5X0.8

