

Digital Thermometers

WIKAI

Digital Thermometers

Type TI.1006DW

- Small Utility
- Digital Readout
- Pocket Thermometer



The Type TI.1006DW is a water-resistant, impact-resistant digital pocket thermometer offering both Fahrenheit and Celsius readings, with a unique "data hold" feature that "remembers" the last reading. Range is from -40° to 300°F and -40° to 150°C and the battery is included.

Standard Features

- **Scale:** As Indicated
- **Range:** °F & °C
- **Stem Length:** 2½"
- **Stem Diameter:** .157"
- **Accuracy:** ± 1% of full range span

Type	T11006DW
List Price	\$33.92
Stem length	2.5"
Range (Fahrenheit & Celsius)	
-40/300°F & °C	N/A

NOTE: Stock items are shown in **bold, blue** print.

Data sheet: [TI.1006DW](#)



Digital Thermometers

Type TI.80/TI.82

- Solar Digital Thermometer
- Easy-to-Read
- R & D Applications



WIKA's solar-powered digital thermometers are ideal for power utilities, petrochemical, and quality control applications, where exact readings are required. TI.80 and TI.82 offers easy-to-read digital temperature in single-degree increments in either Fahrenheit or Celsius scales. TI.80 has a center back mount, while the TI.82 has an adjustable angle, hermetically-sealed case.

Standard Features

- **Case:** 304 Stainless Steel
- **Stem:** 304 Stainless Steel, lengths from 1" to 24"
- **Window:** Glass standard, acrylic available
- **Connection:** ½" NPT, others available
- **Sensor System:** Ceramic Thermistor requiring lighting of only 35 LUX to operate the 3-volt solar cell. The circuitry offers a fast 15-second update time and accuracy to within 1% of scale. A patented safety circuit prevents false readings.

- **Accuracy:** ± 1% of full range span

Note: TI.80/TI.82 are made to order

Just-Rite Adjustable Angle			
	Range -50° to 300°F	Range -50° to 150°C	
Stem Length	Part Number	Part Number	List Price
2½"	82025D2G4	82025D1G4	\$238.92
4"	82040D2G4	82040D1G4	\$238.92
6"	82060D2G4	82060D1G4	\$238.92
9"	82090D2G4	82090D1G4	\$238.92
12"	82120D2G4	82120D1G4	\$238.92
15"	82150D2G4	82150D1G4	\$260.63
18"	82180D2G4	82180D1G4	\$260.63
24"	82240D2G4	82240D1G4	\$260.63

Back Connected			
	Range -50° to 300°F	Range -50° to 150°C	
Stem Length	Part Number	Part Number	List Price
2½"	80025D2G4	80025D1G4	\$188.20
4"	80040D2G4	80040D1G4	\$188.20
6"	80060D2G4	80060D1G4	\$188.20
9"	80090D2G4	80090D1G4	\$188.20
12"	80120D2G4	80120D1G4	\$188.20
15"	80150D2G4	80150D1G4	\$209.92
18"	80180D2G4	80180D1G4	\$209.92
24"	80240D2G4	80240D1G4	\$209.92

Options			
	Code	Description	List Price
Connection	0	Plain	\$3.15
	2	¼" NPT	\$3.15
	3	3/8" NPT (80 only)	\$5.67
Window	A	Acrylic	\$2.94
Accessories	ST	Sharp Tip	\$3.78
	SS	316 SS wetted parts	\$32.66
Stem	HD	3/8" dia. stem w/ 2½" L x ¼" dia tip	\$34.23 for 1st 6" length; \$6.30 for each add'l 6" or part of
	HS	3/8" dia. stem w/ 2 ½" L x ¼" dia. sharp tip	\$34.23 for 1st 6" length; \$6.30 for each add'l 6" or part of

Data sheet: TI.80/TI.82

call 1-888-WIKA-USA or visit www.wika.com

DAUGHTRIDGE SALES Co., Inc.
800-967-7507

